Finger Pulse Oximeter



Features

- Measure SpO2 and PR accurately
- Two color **OLED** screen
- 4 directions display mode
- Real-time spot-checks
- Pulse waveform & bar-graph display
- Advanced setting for **alarm**
- Functions of **audio alarm** and pulse sound
- Automatic power off
- Low power consumption
- **50 hours** continuous to work

Techinical Specifications

Display Type: OLED SPO2: Measurement range: 70-99% Accuracy: 80%-99%, ±2%; 70%-80%,±3%; ≤69% no definition. Pulse Rate: Measure range : 30-235 BPM Accuracy : 30~99bpm, ±2bpm; 100~235bpm, ±2% Pulse Intensity: Bar-graph Indicator **Power Requirements:** Two AAA alkaline Batteries Power consumption: Less than 40mA Low power indication: Battery Life: Two AAA 1.5V, 600mAh alkaline batteries could be continuously operated as long as 30 hours. **Dimension:** Length: 56mm~62mm Width: 32mm~38mm

Height: 34mm~38mm

Weight: 45g~60g (including two AAA batteries)

Environment Requirements:

Operation Temperature: 5~40°C

Storage Temperature: -20~55°C

Ambient Humidity: ≤80%, no condensation in operation.

≤93%, no condensation in storage



Power: 2*AAA (1.5V)


vears Guarantee



Silicon layer on the SpO2sensor

Meditech Equipment Co., Ltd (Meditech Group)

Address: Nanjing Road No.100, Qingdao, Shandong Province, P. R. China China Tel: 86-532-85832673 81705331 Fax: 86-532-81705332 Email: sales@meditech.cn USA Tel: +01 2399355088 UK Tel: +44 2081233737 Web: www.meditech.com.cn



Settings		
Alarm Sound		on
SPO2 Lo		+ 98 -
PR HI		+ 85 -
PR Lo		+ 60 -
Beep		on
	Exit	
-		